

Macs Coral Automatic Security Bollards



- Available in 500mm (1050 and 1051) or 800mm heights (1080 and 1081)
- Hydraulic pump integrated within bollard for ease of installation and increased reliability and intensive use.
- Suitable for use on both low usage residential applications and high usage commercial sites.
- Manual override allows for safe lowering in case of power failure.

EXPERT DESIGN

Popular commercial and residential range of security bollards.

VISUAL SAFETY

Optional LED lights integrated into bollard cylinder (1051 and 1081 models)

CUSTOM FINISH

Available in variety of RAL painted finishes.

Bollard Specifications

Moving Cylinder Diameter	100mm
Moving Cylinder Height (1050 / 1051)	500mm
Moving Cylinder Height (1080 / 1081)	800mm
Cylinder Thickness	5mm
Moving Cylinder Steel Finish	Powder Coated – Standard Anthracite
Reflective Adhesive Strip	Yes
Rising/Lower Speed (1050 / 1051)	4 seconds
Rising/Lower Speed (1080 / 1081)	6 seconds
Connection Cable to Control Unit	Standard 10mt
Hydraulic Pump	Built-In to Bollard
Type of Use	Residential / Commercial
	53 cycles per hour, 154,00 cycles per year (1050 / 1051)
	50 cycles per hour, 146,00 cycles per year (1080 / 1081)

Macs Automated Bollard Systems Ltd
Unit 8.1b Tameside Business Park
Windmill Lane, Denton
Manchester, M34 3QS

Tel: 0161 3206462
Email: enquiries@macs-bollards.com
Web: www.macs-bollards.com