

## Macs BG94 Industrial Security Barrier

### INTENSIVE USE

Industrial security barrier, with 80% duty cycle and in built limit switches, for reliability and high performance. Available in length up to 8M

### EASE OF INSTALLATION

Comes with in-built and pre-wired control panel, making installation quick and simple.



- Industrial use barrier, with built-in opening/closing limit switches
- Integrated control board, pre wired for ease of installation
- 80% duty cycle, ensuring lasting performance and intensive use.

### Barrier Specifications

Barrier Material	Steel Frame, Cataphoresys and RAL Painted
Barrier Motor	230Vac, Single Phase – 50/60Hz – 250W – 1.2Amp
Protection Degree	IP54
Opening Time	12s
Duty Cycle	80%
Max Torque	70Nm
Moving Bar Length	Max 8 M (6M with skirt)
Barrier Weight	80Kg (Without Boom)
Operating Temperature	-20°C +70°C
Type of Use	Intensive
Emergency Release	Yes

Macs Automated Bollard Systems Ltd  
Unit 8.1b Tameside Business Park  
Windmill Lane, Denton  
Manchester, M34 3QS

Tel: 0161 3206462  
Email: [enquiries@macs-bollards.com](mailto:enquiries@macs-bollards.com)  
Web: [www.macs-bollards.com](http://www.macs-bollards.com)